

POSITIONING LASER GREEN Ø 40 MM



DPSS Laser with green laser line. Green lasers are with the same performance for the human eye better obviously as red lasers.

Wood, Stone, Paper etc.

Wood saws, Stone saws, etc.

in illuminated areas or rooms, from 40 mW with sunlight or big line lengths with bright lighting.

Reference	Wavelength	Power	Line	Dimensions
PI-G 532/1	532 nm	1 mW	Dot	ø 40 x 310mm
PI-G 532/5	532 nm	5 mW	2-4 m	ø 40 x 310mm
PI-G 532/10	532 nm	10 mW	3-5 m	ø 40 x 310mm
PI-G 532/15	532 nm	15 mW	5-7 m	ø 40 x 310mm
PI-G 532/25	532 nm	25 mW	6-8 m	ø 40 x 310mm
PI-G 532/40	532 nm	40 mW	8-12 m	ø 40 x 310mm

Holders: BZ40
Optic: Point-optic Angle-optic 60° Angle-optic 90° Powerline
Battery Pack: 4,8V Accu-pack with charger

Lifetime.....	+/- 20,000 Hours
Wavelength.....	532 nm
Power	1 - 40 mW
Weight	1.0 kg
Input	85 - 265 V AC/ 48V AC 12 - 30V DC/ 48V DC
Isolation Class.....	IP 64
Laser Class.....	2/2 M/3B
Work temperature.	- 15 - + 60° C
Stock temperature.	- 40 - + 80° C
Air moisture	0 - 85 %
Power Consumption:...	2.5 W
Warranty.....	24 months



IG-Lasertechnik
Industriestraße 7
D- 53909 Zülpich
Tel. +49(0)2252-8360190
Fax. +49(0)2252-8360191
DE 195 533 141
info@igl.com.de
www.igl.com.de